

EnduraTile™

EnduraTile is a Gypsum core lay-in ceiling tile uniquely incorporating a polypropylene laminate on the exposed face. As opposed to traditional vinyl offerings this provides increased durability in commercial applications.

The durable white fine textured laminate facing provides an easy surface to clean and resistance to discolouration. EnduraTile is suitable for commercial and retail applications where long term durability is required.

ADVANTAGES

- Durable, scratch resistant laminate finish
- Humidity resistant tile, moisture resistant face laminate
- Low maintenance - easy to clean, non-staining
- Excellent resistance to discolouration
- Simple installation

PERFORMANCE DETAILS

EnduraTile was subjected to test procedures described in AS/NZS 3837: 1998 ‘Method of test for heat and smoke release rates for materials and products using an oxygen consumption calorimeter’ for the purpose of determining the Group classifications in accordance with National Construction Code (NCC) volume one specifications C1.10 and A2.4 of the Building Code of Australia (BCA).

- Fire tested to achieve the least fire hazard Group Number for wall and ceiling materials as defined by BCA. BRANZ assessment No. FH 5126.



SPECIFICATION

Feature	Description
Thickness	10mm
Sheet Size (width x length)	592 x 1192mm (metric)
Edge	Square edge
Weight	6.9 kg/m ² nominal
Colour	Matt white finish (low sheen fine textured)
Grid	Exposed
Finish - Face	Polypropylene laminate
Finish - Back	Liner paper
NRC	N/A
CAC	35 without insulation
Core	High density Gypsum core
Light Reflectance	0.79
Fire Hazard Properties	Group 1 - in accordance with BCA Specification C1.10a Fire Hazard Properties - Floors, Walls and Ceilings
Combustibility	Non Combustible material as defined in BCA Deem-to-Satisfy Provisions C1.12
VOC	Less than 0.5mg/m ² /hr
GECA	N/A
Manufacture	Manufactured in Australia to the requirements of AS/NZS 2588:1998 Gypsum plasterboard and in accordance with AS/NZS ISO 9001:2008 - Quality management systems - Requirements

INSTALLATION

Refer to USG Boral website USGBoral.com
or call TecASSIST® on 1800 811 222.

WASTE MANAGEMENT

Waste collection services are available to divert acceptable plasterboard waste away from land fill for recycling or re-processing for other uses. For information on waste collection services available, please contact your local USG Boral office.

VOLATILE ORGANIC COMPOUNDS (VOC) AND FORMALDEHYDE MINIMISATION

USG Boral products, compounds and adhesives have been independently tested to confirm compliance with Green Star specification limits for VOCs and are formaldehyde free. Emission Test Certificate CV080415.

REFERENCES

Refer USGBoral.com for Material Safety Data Sheet, Volatile Organic Compound Emission details and Fire Test Report information. For Ceiling Tile range, refer to USGBoral.com/ceilings

SALES ENQUIRIES **1800 003 377**

TecASSIST® **1800 811 222**