

# USG TRANSLUCENTS™ LUMINOUS INFILL PANELS



USG Translucents™ Luminous Infill Panels/USG Donn® Brand Centricitee™ DXT™ Acoustical Suspension System

## TO ORDER SAMPLES, GO TO USG.COM

See IC603 for Color Gallery availability.

### NATURAL



Natural Leaves™



Search-light™



Paper Leaf™



Woodland Print™

### WOVEN



Luna Ice™



Artichoke™



Iris™



Butter-scotch™

### TEXTILES



White Fiberoptic™



Matrix II™



Avanti™



Meander Lipstick™



Meander White™



Beige Interlock™



White Mesh™

### EMBOSSSED



Ovalesque Frost™



Rain™



Silver Spun™

### METALLIC

### COLOR GALLERY



**New!** See IC603 for 24 new colors.

## FEATURES AND BENEFITS

- Fully accessible translucent (luminous) infill panels.
- Panels can be used with standard USG Donn® Brand DX\*/DXL™, Centricitee™ DXT™, Curvatura™ 3-Dimensional and GridWare™ Open Cell Decorative suspension systems.
- Available in 6 finishes: Natural (4 color choices), Woven (3 color choices), Industrial (2 color choices), Shimmer (2 color choices), Textiles (7 color choices) and Embossed (2 color choices).
- 2'x2' panels (23-3/4"x23-3/4") in all finishes.
- 2'x6' panels (23-3/4"x71-3/4") in all finishes.
- Woven, Shimmer, Textiles, Industrial and Natural finishes contain a minimum 40% recycled content.
- Embossed acrylic panels contain a minimum of 50% recycled content.
- Coordinating suspension and trim colors as well as larger color swatches can be found on the USG Translucents™ Finishes page (IC552).

## APPLICATIONS

- Lobbies
- Contemporary office environments
- Entertainment
- Gaming
- High-bay areas
- Retail stores



# USG TRANSLUCENTS™ LUMINOUS INFILL PANELS

ORDER SAMPLES/LITERATURE  
usg.com | [sampkit@usg.com](mailto:sampkit@usg.com)  
fax: 888 874-2348

TECHNICAL SERVICES  
800 USG.4YOU (874-4968)

SEE LEED REPORT TOOL  
for detailed sustainability  
information, as well as the  
**MOST UP-TO-DATE**  
TECHNICAL INFORMATION,  
at [usgdesignstudio.com](http://usgdesignstudio.com)

## PRODUCT INFORMATION

Materials	Typical Sizes		System Weight
	Nominal	Actual	
Clear Mat	2'x2'	23-3/4"x23-3/4"	Approximately 0.9 lbs./sq. ft.
Woven, Shimmer, Textiles, Natural, Industrial – 0.118" PETG	2'x2' 2'x6'	23-3/4"x23-3/4" 23-3/4"x71-3/4"	Approximately 0.9 lbs./sq. ft.
Embossed Acrylic	2'x2' 2'x6'	23-3/4"x23-3/4" 23-3/4"x71-3/4"	Approximately 0.9 lbs./sq. ft.
Color Gallery	2'x2' 2'x6'	23-3/4"x23-3/4" 23-3/4"x71-3/4"	Approximately 0.9 lbs./sq. ft.

This product does not offer any acoustical properties.

For USG Translucents™ panels, fluorescent strip fixtures should be placed a minimum of 18" above the ceiling and 18" o.c. for best results.

Lays into standard USG Donn® Brand DX\*/DXL™, Centricitee™ DXT™, Curvatura™ 3-Dimensional and GridWare™ suspension systems.

Acoustics  
Lighting  
Suspension Systems

## FOR MORE INFORMATION

### Product literature

Data sheet: IC406

### Online tools

[usgdesignstudio.com](http://usgdesignstudio.com)

This product is produced to order and will vary from batch-to-batch – panels ordered at the same time will be produced together and will be identical. USG cannot guarantee batch-to-batch consistency.

### Code approval

USG Translucents™ panels meet Class B requirements for flame spread and smoke developed as defined by ASTM 1264 and as tested in accordance with ASTM E84. (40/175) USG Translucents™ panels also meet Class A requirements of NFPA and IBC (UBC) as interior finishes, not to be part of an air supply/return system. Designers and installers are advised to consult a fire protection engineer, NFPA 13 and their local codes for guidance where automatic fire detection and suppression systems are present.

### Weight

0.374 lbs./sq. ft.  
(Glass Green Matte and Clear Matte)  
0.90 lbs./sq. ft.  
(Woven, Textiles, Shimmer, Natural,  
Industrial, Embossed)

### Recycled content

Woven, Textiles, Shimmer, Natural,  
Industrial panels: min. 40% recycled  
content. 100% recyclable. Embossed  
panels: 50% recycled content. 100%  
recyclable. Color Gallery: Up to 40%  
recycled content.