

USGBoral EasyPlus

USGBoral EasyPlus is a high performance Air drying compound used for treating gypsum board joints and fixing points.

JOINTING COMPOUND



EasyPlus provides excellent tape bonding strength, is exceptionally smooth to work with and the easy mixing saves time. EasyPlus is relatively easy to sand, giving a high level of finish.

Product Usage Data :

Air Drying Compound	
Mixing Ratio	2 parts of compound to 1 part of water (in kg.)
Storage	The product must be kept in dry conditions, away from moisture. The bag should be stored at an elevated position. Part open bags should be sealed, as moisture can accelerate the setting time.

Mixing procedure :




1. Always use clean water, tools and containers. Using dirty containers / tools may affect setting time.



2. Slowly add powder to water.


Tapered Edge Joints (3 easy steps) :

1st Coat




Apply EasyPlus of 150 mm width for joint reinforcement.

2nd Coat




Apply an even coat of EasyPlus of 200 mm width.

3rd Finishing Coat




Apply an even coat of **EasyPlus** of 300 mm width for finishing.


Square Edge Joints (3 easy steps) :



Apply EasyPlus of 300 mm width for joint reinforcement.



Apply an even coat of **EasyPlus** of 400 mm width.



Apply an even coat of **EasyPlus** of 500-600 mm width for finishing.

Note : All Gypsum board Joints require light sanding before painting.

*Available in 25 kg bag