

OLYMPUS™ CLIMAPLUS™ CONCEALED / SEMI-CONCEALED



Olympus Panels with Climaplus Performance / DA Suspension System

FEATURES AND BENEFITS

- Fine-textured acoustic panels, creates a clean and upscale appearance
- High reflectivity, decreases lighting requirement, saves energy, alleviates eye fatigue
- Features a sharp, monolithic look

APPLICATIONS

- Closed/Open type offices
- Retail stores
- Hospitals
- Warehouses
- Schools/Auditoriums
- Restaurants
- Exhibition rooms
- Light industrial buildings

SUBSTRATE

- Water-felted mineral fiber

 High Recycled Content

Fine-textured panel - Perforated



OLYMPUS™ CLIMAPLUS™ CONCEALED / SEMI-CONCEALED

USGBORAL.COM

OLYMPUS CLIMAPLUS PANELS

Edge	Panel Size ³	Class	Item No.	NRC	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew	Recycled Content ¹	
(Long side) S-BESK 	300 x 1200 x 15mm ⁴	Class A	ME400375	.55	33	.85	White	A	Low		60%	
	300 x 1800 x 15mm ⁴	Class A	ME400575	.55	33	.85	White	A	Low		60%	
	(Short side) SQ 	400 x 1800 x 15mm ⁴	Class A	ME401075	.55	33	.85	White	A	Low		60%
	300 x 1800 x 19mm ⁴	Class A	ME400570	.60	33	.85	White	A	Low		42%	
	300 x 2400 x 19mm ⁴	Class A	ME400770	.60	33	.85	White	A	Low		42%	
	400 x 1800 x 19mm ⁴	Class A	ME401070	.60	33	.85	White	A	Low		42%	
	400 x 2400 x 19mm ⁴	Class A	ME401270	.60	33	.85	White	A	Low		42%	
(Long side) BESK 	300 x 1200 x 15mm ⁴	Class A	ME400365	.55	33	.85	White	A	Low		60%	
	300 x 1800 x 15mm ⁴	Class A	ME400565	.55	33	.85	White	A	Low		60%	
	(Short side) SQ 	400 x 1800 x 15mm ⁴	Class A	ME401065	.55	33	.85	White	A	Low		60%
	300 x 1800 x 19mm ⁴	Class A	ME400560	.60	33	.85	White	A	Low		42%	
	300 x 2400 x 19mm ⁴	Class A	ME400760	.60	33	.85	White	A	Low		42%	
	400 x 1800 x 19mm ⁴	Class A	ME401060	.60	33	.85	White	A	Low		42%	
	400 x 2400 x 19mm ⁴	Class A	ME401260	.60	33	.85	White	A	Low		42%	
(Long side) S-BESK 	300 x 1200 x 15mm ⁴	Class A	ME400385	.55	33	.85	White	A	Low		60%	
	300 x 1800 x 15mm ⁴	Class A	ME400585	.55	33	.85	White	A	Low		60%	
	(Short side) BESK 	400 x 1800 x 15mm ⁴	Class A	ME401085	.55	33	.85	White	A	Low		60%
	300 x 1800 x 19mm ⁴	Class A	ME400580	.60	33	.85	White	A	Low		42%	
	300 x 2400 x 19mm ⁴	Class A	ME400780	.60	33	.85	White	A	Low		42%	
	400 x 1800 x 19mm ⁴	Class A	ME401080	.60	33	.85	White	A	Low		42%	
	400 x 2400 x 19mm ⁴	Class A	ME401280	.60	33	.85	White	A	Low		42%	

LEGEND

Low Emission (VOC Class)

ClimaPlus Superior Performance

High Recycled Content

≥ .85 LR

Meets the emission test criteria as low-emitting prescribed by the Singapore Green Building Council (SGBC), following ASTM D5116-06 testing methods

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew

Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

GRID PROFILE OPTIONS

A
DA
DXI
DXII



PHYSICAL DATA/ FOOTNOTES

ASTM E1264 Classification
Type III, Form 2, Pattern C,E

ASTM E84 surface burning characteristics
Class A

Flame spread: 25
Smoke developed: 50

Imperial Weight
0.94-1.16 lb./ft.²

Metric Weight
4.6-5.7 kg/m²

Short Specification:

- * Ceiling system shall comprise USG Olympus™ ClimaPlus™ Concealed / Semi-Concealed high humidity / fire resistant acoustical ceiling panels in DA, DXI and DXII
- * Panels shall have NRC 0.55 / 0.60.
- * Panels shall have CAC 33.
- * Nominal size (15mm x 300mm x 1200mm / 1800mm, 15mm x 400mm x 1800mm, 19mm x 300mm x 1800mm / 2400mm, 19mm x 400mm x 1800mm / 2400mm). Imperial equivalent size available
- * Edge detail shall be Shiplap-Bevel Edge Standard Kerf & Square (S-BESK & SQ) / Bevel Edge Standard Kerf & Square (BESK & SQ) / Shiplap-Bevel Edge Standard Kerf & Bevel Edge Standard Kerf (S-BESK & BESK).
- * Limiting Conditions - Maximum 49°C (120°F)/99% RH.

Thermal Resistance
R-1.7

Backloading
Refer to Installation and Maintenance

Maintenance
Can be cleaned easily with a soft brush or vacuum.

Footnotes

- For details, see LEED report tool at usgdesignstudio.com.
- LR values are shown as averages.
- Not all panel size available in all geographic areas, some metric sizes available to order.
- Imperial equivalent size available.

TRADEMARKS

The trademarks CENTRICITEE, CLIMAPLUS, DONN, DX, DXF, DXFF, DXM OMEGA, DXT, FINELINE, DA OLYMPUS, CATERPILLAR, NEW STAR-Z, EXCEL, PIN PERF and INNOVATION INSPIRED BY YOU are trademarks of USG Boral Building Products or one of more of its affiliates.

SAFETY FIRST!

Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

ACT 15 2015 / 7-15

© 2015 USG Boral. All rights reserved.

Manufactured, sold or distributed by USG Boral Building Products or one of more of its affiliates.
Persiaran Lagoon, Bandar Sunway, Petaling Jaya, Selangor, Malaysia 46150

USG BORAL SINGAPORE
8 Boon Lay Way #02-06 TradeHub 21
Singapore 609964
Tel: (65) 6272 9272 Fax: (65) 6278 5310



041-001-2474
Made From Recycled Material

www.usgboral.com

USG BORAL